

INDUSTRIAL INTEGRATED WORKSTATION





HW | Enclosed Unit with Integrated PC

DYNICS HW is an integrated PC housed in a fully sealed metal enclosure for industrial applications. This fan-less system includes a Braswell motherboard and resistive touch screen capability.

- NEMA 4 / NEMA 4X
- IP65/66

• 100~240VAC (3-Pin) / 24VDC (4-Pin)

VESA / Wall Bracket Mount System with Up to 0°-20° Tilt

DISPLAY SPECIFICATIONS

RESOLUTION
VIEW ANGLE
CONTRAST
BRIGHTNESS
ASPECT RATIO
LENS
LCD LIFE
ENCLOSURE

12.1"	15.6"	18.5"	21.5"	24"
WXGA 1280 x 800	FHD 1920 x 1080			
H: -80°/+80°	H: -80°/+80°	H: -85°/+85°	H: -89°/+89°	H: -89°/+89°
V: -80°/+80°	V: -80°/+80°	V: -80°/+80°	V: -89°/+89°	V: -89°/+89°
800:1	800:1	1500:1	5000:1	3000:1
400 nits	600 nits	400 nits	300 nits	300 nits
16:9	16:9	16:9	16:9	16:9

5-Wire Analog Resistive (Touch Screen) / Protective Polycarbonate Lens (Non-Touch)

50,000 Hour Backlight Half-Life

NEMA 4 Powder Coat Finish/ RAL 7035 Peel Finish / NEMA 4X Stainless Steel

0-20° Tilt Bracket included with 60,100,150,200, & 250 VESA mounts (can also be used for wall mounting)

PC SPECIFICATIONS

COMPUTER I/O 1Gb Ethernet Ports USB 3.0 Ports CPU CPU SPEED

MEMORY STORAGE OPERATING SYSTEM POWER SUPPLY TEMPERATURE

RELATIVE HUMIDITY SHOCK RESISTANCE

VIBRATION

INCLUDED COMPLIANCE WARRANTY

Intel® Apollo Lake	Whiskey Lake 8th Gen Intel®
2x	2x
2x	2x
Intel® Apollo Lake N3350 / N4200	Intel® Core™ i5 8265U / i7 8565U
N3350 - 2.4 GHz, 2MB Cache (2 Cores, 2 Threads)	i5 – up to 3.9GHz, 6MB Cache (4 Cores, 8 Threads)
N4200 - 2.5 GHz, 2MB Cache	i7 – up to 4.6GHZ, 8MB Cache
(4 Cores, 4 Threads)	(4 Cores, 8 Threads)
Up to 64GB DDR4	Up to 64GB DDR4

256GB – 2TB SATA SSD / 1TB HDD

-Windows® 10 Enterprise IoT LTSC 2019 (64-bit) 100~240VAC (3-Pin) / 24VDC (4-Pin) Power Entry

Operating: 0°-50°C | 32°-122°F

Non-Operating: -25°-60°C | -13°-140°F

Non-Condensing: 20% - 80%

Operating: 10G Non-Operating: 15G

Operating: 1.0G from 57~2000Hz Non-Operating: 2.5G from 57~2000Hz

1x 6 ft. Power Cable

European Union Directive 2011/65/EU (RoHS)

24-Month limited warranty. Extended warranty available, contact DYNICS for more details.

















INDUSTRIAL INTEGRATED WORKSTATION






DIMENSIONS, WEIGHT AND POWER CONSUMPTION

	12.1	15.6"	18.5"	21.5"	24"
HEIGHT	9.0"	11.8"	13.1"	15.0"	15.4"
	(228.6mm)	(298.5mm)	(331.5mm)	(381.8mm)	(402.1mm)
WIDTH	13.9"	17.5″	19.8"	22.6"	24.9"
	(352.3mm)	(445.5mm)	(503.1mm)	(574.2mm)	(630.3mm)
DEPTH	2.5"	6.0"	6.0"	6.0"	6.0"
	(63.3476mm)	(150.8mm)	(150.8mm)	(150.8mm)	(150.8mm)
WEIGHT	7lbs*	15 lbs.*	20 lbs.*	24 lbs.*	26 lbs.*
POWER CONSUMPTION	35 Watts**	40 Watts**	45 Watts**	55 Watts**	85 Watts**

^{*}Weights are approximate, contact DYNICS for details.


MECHANICAL DRAWINGS FRONT VIEW



SIDE VIEW




BACK VIEW



POWER ENTRY

(3-Pin) 100~240VAC

(4-Pin) 24VDC



1 GROUND 2 LINE 3 NEUTRAL



- 1 NO CONNECT 2 0 VDC
- 3 NO CONNECT
- 4 +24 VDC















^{**}Power Consumption based on maximum ratings, actual ratings vary significantly based on components used.