



HSW

HSW | Enclosed Unit with Integrated PC

DYNICS HSW is a fully sealed integrated workstation in an IP66 rated enclosure built to withstand water and ambient pollutants. The HSW is equipped with either an Apollo Lake or Whiskey Lake quad core processor, making it a highly proficient workstation for food grade applications in caustic environments.

- 24VDC (4-Pin)
- Overlay Touch Screen
- NEMA 4X Stainless Steel 316 Food Grade
- VESA/Wall Mount Bracket Mount System with Up to 20° Tilt

DISPLAY SPECIFICATIONS

	15.6"	18.5"
SIZE	15.6"	18.5"
RESOLUTION	FHD 1920 x 1080	FHD 1920 x 1080
VIEW ANGLE	H: -80°/+80° V: -80°/+80°	H: -85°/+85° V: -80°/+80°
CONTRAST	800:1	1500:1
BRIGHTNESS	600 nits	400 nits
ASPECT RATIO	16:9	16:9
LENS	Overlay Analog Resistive Touchscreen	
LCD LIFE	50,000 Hour Backlight Half-Life	
ENCLOSURE	NEMA 4X Stainless Steel 316 Food Grade / IP66 0-20° Tilt Bracket included with 60, 100, 150, 200, & 250 VESA mounts (can also be used for wall mounting)	

PC SPECIFICATIONS

	Intel® Apollo Lake	Intel® 8 th Gen Whiskey Lake-U
COMPUTER I/O	2x	2x
1Gb Ethernet Ports	2x	2x
USB 3.0 IP65 Ports		
CPU	Apollo Lake Quad Core™ Pentium® N4200	Intel® 8th Gen Core™ i5 8265U / i7 8565U
CPU SPEED	Up To 2.5GHz, 2MB Cache (4 Cores, 4 Threads)	i5- up to 3.9 GHz, 6MB Cache (4 cores, 8 threads) i7- up to 4.6 GHz, 8MB Cache (4 cores, 8 threads)
MEMORY	Up to 16GB DDR3	Up to 32GB DDR4
STORAGE	256GB – 2TB SATA SSD / 1TB HDD	
OPERATING SYSTEM	-Windows® 10 Enterprise IoT LTSB 2016 (64-bit) <i>(Only available with Apollo Lake)</i> (Code: E10) -Windows® 10 Enterprise IoT LTSC 2019 (64-bit) (Code: E19) - Windows® Pro 10 (64-bit) (Code: W10) -Windows® 10 Enterprise IoT LTSC 2021 (64-bit) (Code: E21) - Windows® Pro 11 (64-bit) (Code: W11) -Linux® Ubuntu® - Contact DYNICS for more details (Code: LUB)	
POWER SUPPLY	24VDC (4-Pin) Power Entry (Quick Disconnect Included)	
TEMPERATURE	Operating: 0°-45°C 32°-113°F Non-Operating: -25°-60°C -13°-140°F	
RELATIVE HUMIDITY	Non-Condensing: 20% - 80%	
SHOCK RESISTANCE	Operating: 10G Non-Operating: 15G	
VIBRATION	Operating: 1.0G from 57~2000Hz Non-Operating: 2.5G from 57~2000Hz	
ALTITUDE INCLUDED	Maximum altitude of 2,000 meters	
OPTIONAL COMPLIANCE	1x (4-Pin) Quick Disconnect VESA Bracket Mount System D-Coded M12 Ethernet Connector / X-Coded M12 Ethernet Connector / RJ45 Capped Ethernet Connector	
WARRANTY	European Union Directive 2011/65/EU (RoHS) 24-Month limited warranty. Extended warranty available, contact DYNICS for more details.	





HSW


DIMENSIONS, WEIGHT AND POWER CONSUMPTION

	15.6"	18.5"
HEIGHT	11.75" (298.5mm)	13.05" (331.5mm)
WIDTH	17.54" (445.5mm)	19.80" (503.1mm)
DEPTH	3.39" (86.2mm)	3.39" (86.2mm)
DEPTH (With VESA Bracket)	6.90" (175.1mm)	6.90" (175.1mm)
WEIGHT	28.3 lbs.*	30.0 lbs.*
POWER CONSUMPTION		
Apollo Lake	40 Watts**	60 Watts**
Whiskey Lake	50 Watts**	65 Watts**


*Weights are approximate, contact DYNICS for details.

**Power Consumption based on maximum ratings, actual ratings vary significantly based on components used.


MECHANICAL DRAWINGS FRONT VIEW




SIDE VIEW



BACK VIEW



POWER ENTRY



ISOMETRIC VIEW

